



2.700 - 2.900 MHz Parabolic Grid

Designed to deliver performance for decades

Features

- Lightweight and durable construction.
- Feed input Type N as shown, others noted below.
- Parabolic Grid designs typically offer 40% lower wind-loading, when compared to a like sized solid antenna without ice.
- Feed guy supports are included when necessary.
- Antenna features independent azimuth and elevation adjustment.
- Antenna Survival Ratings: 1 inch (25mm) of ice and 125 mph (201 kmh) wind.
- Antenna Mount Types:
 - Standard (S) mounts** mate to a 4.5 in. O.D. (114 mm) (4 in. IPS) vertical pipe mast. Available on 6-ft. – 15-ft. (1.8-m – 4.6-m)
 - Universal (U) mounts** mate to 1.9 in.– 4.5 in. O.D. (48 mm – 114 mm) vertical pipe mast. Available on 4-ft. – 6-ft. (1.2-m – 1.8-m)
- All mWAVE – Mark Grid Series antennas meet or exceed Standard ANSI/TIA-222.



mWAVE supports all current and legacy Mark parabolic grids with feeds, wind brace kits and other miscellaneous parts and tuning services.

Electrical Specifications

Frequency MHz	Model No.	Pol.	Size		Reg.	Gain, nominal dBi			HPBW Deg.	XPD dB	F/B dB	VSWR max	R.L. dB
			ft.	m.		Low	Mid	High					
2.700 – 2.900	P-28B36GN-U	LP	3	0.9	-	24.9	25.3	25.6	8.0	35	32	1.5:1	14.0
2.700 – 2.900	P-28B48GN-U	LP	4	1.2	-	27.4	27.7	28.0	6.0	35	35	1.5:1	14.0
2.700 – 2.900	P-28B72GN-U	LP	6	1.8	-	29.2	29.5	29.8	4.0	35	40	1.5:1	14.0
2.700 – 2.900	P-28B72GN-S	LP	6	1.8	-	29.2	29.5	29.8	4.0	35	40	1.5:1	14.0

Notes: * Optional input connectors available.
 F = 7/8 EIA Flange Non-pressurized
 P = 7/8 EIA Air Dielectric Non-pressurized
 N = N-Female Connector Non-Pressurized
 E = 7/16 DIN Connector Non-Pressurized
Product information is subject to change without notice.

Designed, Engineered, and Manufactured in Windham, ME USA
 mWAVE Industries is part of the Alaris Holdings Group of Companies.
 © mWAVE Industries LLC - 2023 All rights reserved

Form: 2700-2900-Grid-230130.R2.DS

